



Artifacts™

80-7/8" H sliding shower door with 3/8"-thick glass

K-701726-10L

Features

- Exposed roller design allows for effortless opening and closing of the sliding panel
- Frameless design for an open, airy look
- Back-to-back 16-7/16" (418 mm) vertical handles
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Available in select finishes to match Artifacts faucets and accessories
- Coordinates with other products in the Artifacts collection

Material

- Frameless, heavy 3/8" (10 mm) thick Crystal Clear tempered glass door and in-line panel
- Premium construction for durability and reliability
- KOHLER finishes resist corrosion and tarnishing

Installation

- 80-7/8" (2054 mm) high, with a lofty 76-7/8" (1953 mm) minimum head clearance
- Fits opening widths 46-1/4" – 47-1/4" (1175 – 1200 mm)
- 1" (25.4 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential use only
- Not for use with cast iron shower bases



Codes/Standards




ANSI Z97.1
CAN/CGSB-12.1
CPSC 16CFR 1201

KOHLER® Bath and Shower Doors Ten-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	SN	Vibrant® Polished Nickel
	CP	Polished Chrome
	BN	Vibrant Brushed Nickel

Available Glass Options

Code	Description
L	Crystal Clear



Artifacts™
80-7/8" H sliding shower door with 3/8"-thick glass
K-701726-10L



Technical Information

All product dimensions are nominal.

Shower Ledge Min 2-7/16" (62 mm)
Flat:

Shower Wall Min 3-5/16" (84 mm)
Flat:

Wall Studs Required Yes
for Door:

Notes

Install this product according to the installation instructions.

The vertical opening should be a minimum of 83" (2108 mm) to allow for installation clearance.