



Home / Products / Filters, Collectors, Separators, Purifiers / Filter Assemblies and Vessels / Pleated Filters / Xtreme+Plus® - Standard Size Pleated Filters / 0474717

Xtreme+Plus® - Standard Size Pleated Filters

Part #: 0474743



Technical Specifications

Nominal Filter Size:	16 x 16 x 1 in	Media:	Synthetic
Air Filter Ply:	N/A	Merv Rating:	MERV 8
Application:	Commercial & Industrial	Pleat Separator Type:	Self-Supporting
Brand:	Airguard	Product Type:	Pleated Air Filter
Filter Efficiency Rating:	= 70 % at 3.0 to 10.0 Micron	Rated Air Velocity:	300 ft/min
Filter Type:	Die-Cut Panel	Reusable/Disposable:	DISPOSABLE
Header Size:	n/a	Size:	16 x 16 x 1 in
Materials of Construction:	Moisture Resistant Beverage Board Frame	Specifications Met:	Classified per UL 900 for flammability only
Maximum Operating Temperature:	150		

California Residents: Prop-65 Warning

 Safety Warning

Item Information

The XTREME+Plus® standard-capacity, self-supported pleated (SSP) air filter with Airguard® technology achieves MERV 8 mechanical efficiency and provides low pressure drop and industry-leading dust-holding capacity.

The filter has over 140 adhesion points between the media and the die cut frame. The inside of the frame is completely coated with water-repellant adhesive to ensure a solid bond at all points of contact with the media pack. The pack is sealed inside the frame and pleat tips are bonded to the stabilizers and diagonal support members. This prevents movement, bunching, and collapsing during operation, which can often cause alternative filter products to fail prematurely. With no metal wire backing to warp or deform, along with a single-piece, heavy-duty beverage board frame and rugged self-supported pleat technology, the XTREME+Plus® filter is capable of maintaining its performance and structural integrity in wet or humid conditions. This saves users time and money that is often wasted on replacing damaged wire-backed filters.

XTREME+Plus® pleated air filters are designed for use in commercial HVAC applications with normal operating environments and low to medium dust loading conditions. They are not recommended for use in high-temperature or turbulent-airflow environments.

For XTREME+Plus® air filters with a lower initial resistance (in. w.g.), see the XTREME+Plus® HC (high-capacity).

Markets:

- Commercial and Industrial HVAC
- Process Air Filtration

Applications:

- Air handling systems
- Rooftop units
- Side access housings
- Built-up filter banks
- Pre-filters in multi-stage systems
- Not for use in high temperature environments or applications with very high or turbulent airflow

Benefits:

- Self-supported media — no metal wire backing means no corrosion or deformation of metal
- Consistent pleat shape and spacing allow particulates to collect evenly over the entire surface of the media. Pleat stabilizer straps add rigidity and maintain proper pleat spacing.
- Over 140 adhesion points between the media and the frame
- Achieves MERV 8 mechanical efficiency
- Synthetic media is resistant to moisture, mold, and mechanical damage
- Fully incinerable, environmentally friendly disposal

Features:

- Filtration efficiency: MERV 8, MERV-A 8-A
- Nominal thickness (in.): 1, 2
- Rated air velocities (fpm): 300–500
- Air flow rates (cfm): 415–2170
- Initial resistance (in.w.g.): 0.15–0.22
- Final resistance (in.w.g.): 1.0
- Maximum operating temperature: 150 °F (65 °C)
- Material of construction: single-piece, moisture-resistant, beverage board frame
- Classified per UL 900 for flammability only



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

