



HVAC/R Professional Clamp with DC Amps



We Made It Better!

- Magnetic hanger strap with flexible application
- Easy access battery latches. No screwdriver needed.
- Test lead storage for convenience
- Added selection dial to navigate test functions
- Increased capacitance range to 6000 μ F with faster response times
- Current range to 600A AC/DC (upgrade DL389B 400A AC)
- Back probes included for mini-split applications



All The Pro Features You Love

- Same functionality as our popular DL489
- 13 Key test functions
- More than 15 features

Distinguished In The Marketplace

- 2-Year Limited Warranty
- Professional Safety Ratings

Available For A Great Price!

\$281⁷⁵ TNP

DESIGNED BY
MADE BY
UEi



BACKED BY
UEI
QUALITY

2
YEAR
WARRANTY



Clamp Meter Line Comparison



	DL599	DL589	EPC	DL569+
True RMS	YES	YES	YES	NO
Voltage AC/DC	1000 AC / 1000 DC	750 AC / 1000 DC	750 AC / 1000 DC	750 AC / 1000 DC
Amperage AC/DC	600 AC / 600 DC	600 AC / 600 DC	400 AC	400 AC
Capacitance	9999µF	2000µF	4000µF	4000µF
Resistance	60M	60M	40M	40M
Continuity & Diode Test	YES	YES	YES	YES
AC / DC microamps	2000µA (DC only)	2000µA	2000µA (DC only)	2000µA
Min/Max	YES	YES	YES	YES
Hold	YES	YES	YES	YES
Ranging	Auto/ Man	Auto/ Man	Auto/ Man	Man
Display count	6000	6000	4000	4000
Auto power off	YES	YES	YES	YES
Low battery warning	YES	YES	YES	YES
Test lead storage	YES	YES	YES	YES
Dual display	YES	YES	YES	YES
High voltage alert	YES	YES	YES	YES
Auto Calibration	YES	YES	YES	YES
Easy access battery latches	YES	YES	YES	YES
Temperature (K-type input)	-328 to 2462°F	-328 to 2462°F	-328 to 2462°F	
Frequency (Hertz)	YES	YES	YES	
Duty cycle	YES	YES	YES	
LRA inrush	YES	YES	YES	
Magnetic mount/strap	YES	YES	YES	
Wireless to app	YES	YES	YES	
NCV (LED & Audible)	YES	YES	YES	
Backlight	YES	YES	YES	
Low Z (impedance)	YES	YES	YES	
Worklight	YES	YES		
Temperature differential	YES	YES		
DC Zero	YES	YES		
POWER(W, VA, VAR)	YES			
Power Factor	YES			
Auto AC/DC selection for V/A	YES			
3-Phase motor rotation test	YES			
Motor unbalanced test	YES			
Low pass filter	YES			
Safety Rating	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V
Warranty	2 YEAR	2 YEAR	2 YEAR	1 YEAR

Safety Rated: CATIV 600V / CATIII 1000V
Certified by ETL to IEC 61010-1, 3rd edition



Includes

- Silicone Test Leads (ATL58)
- Alligator Clips (AAC3)
- Temperature Probes 2 (ATT29)
- Zippered Pouch
- Batteries 4 (AAA)
- Manual