



Tel: 800-752-9326
Fax: 763-389-2725
SRWProducts.com

PO Box 70
32005 126th St
Princeton, MN 55371

DF1.5

To Whom It May Concern:

This letter is to certify that SRW Products Manufactures/Supplies a 100% Polyester Non-Woven Thermal Bonded Filament Fibers marketed as **DF1.5**. With excellent dimensional stability and low shrinkage, our drainage fabrics serve as the professional's choice for drain-field projects. The fabric will not rot or mildew, is non-biodegradable with superior UV resistance, and is resistant to damage from insects and rodents.

DF1.5 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight (Typical)	ASTM D 5261	oz/sy	1.5 (50 g/sm)
Grab Tensile	ASTM D 4632	lbs.	50 x 52
Grab Elongation	ASTM D 4632	lbs.	47 x 49
Trap Tear	ASTM D 4533	lbs.	16 x 17
Puncture	ASTM D 4833	lbs.	21.2
Permittivity	ASTM D 4491	sec ⁻¹	Above 2.5
Water Flow	ASTM D 4491	gpm/ft ²	235
AOS	ASTM D 4751	US Sieve	#40

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.