

600 PBR Series Designer RO Faucet



Features:

- Retrofits most brands
- Smooth operating ceramic disk element
- Lever style handle
- High reach neck design of 12" (305 mm)
- Neck swivels 360°
- Protective spout tip prevents after drip
- Patented modular air gap (U.S. patent #7,011,106)
- Base diameter is 2-1/4" (57 mm)
- Two year warranty
- Spout reach is approximately 5" (127 mm)
- Pressure rating: 125 PSI/8.6 BAR
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI/2.32 BAR
- Temperature rating: 40°F/4°C to 150°F/66°C
- 1/4" OD x 30" tubing pre-installed
- Includes installation hardware and instructions

Codes Applicable:

- The 600 PBR Series Designer RO Faucet is certified to NSF/ANSI Standard 61 – Annex G. These Designer RO Faucets are low-lead plumbing products and are in compliance with California's Health and Safety Code (Section 116875; commonly known as AB1953).
- Compliant with pending revisions to the USEPA Safe Drinking Water Act with effectivity January 4, 2014.
- ADA Compliance - ANSI A117.1

Colors/Finishes:

- Polished chrome (#1019299)
- Satin nickel (#1019301)
- White (#1019303)
- Biscuit (#1019305)
- Polished brass (#1019309)
- Antique bronze (#1019311)
- Black (#1019307)
- Bright nickel (#1019444)
- Brushed Stainless (#1020518)
- Venetian Bronze (#1024293)
- Polished Nickel (#1025811)

Common Replacement Parts:

- Cartridge (#1917362)

Technical dimensions on reverse side.

Technical dimensions on reverse side.

www.tomlinsonind.com



Certified to NSF/ANSI 61
Section 5-G



