

# Sliding shower door, 70-1/2" H x 56-1/4 - 59-5/8" W **K-707608-6D3**

#### **Features**

- Frameless design emphasizes glass and creates a sleek, minimalist look
- Vertical handle with inside knob on moving panel
- Gently-curved towel bar provides integrated storage on fixed panel
- Tempered glass ensures enhanced safety and durability
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Smooth, easy-to-clean wall jambs
- Full-length moving panel seal provides excellent water containment
- Upgrade to heavy 5/16" (8 mm) thick glass and tall height shower door by selecting K-707615-8G81
- Coordinates with other products in the Elate collection
- Shower door configuration consists of one sliding panel and one stationary panel

#### Material

- Frameless, 1/4" (6 mm) thick Frosted tempered glass
- Anodized aluminum prevents rust and corrosion

#### Installation

- Fits opening widths 56-1/4" 59-5/8" (1429 1514 mm)
- 70-1/2" (1791 mm) high, with 67-11/16" (1719 mm) minimum head clearance
- 3-3/8" (86 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential use only
- Not for use in hospitality



#### Codes/Standards

ANSI Z97.1 CAN/CGSB-12.1 CPSC 16CFR 1201

### **KOHLER® Bath and Shower Doors Ten-Year Limited Warranty**

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.


Color	Code	Description
	SH	Bright Silver
	MX	Matte Nickel
	BL	Matte Black

## Available Glass Options Code Description

D3 Frosted



# Sliding shower door, 70-1/2" H x 56-1/4 - 59-5/8" W **K-707608-6D3**



### **Technical Information**

All product dimensions are nominal.

Base-To-Wall 1/2" (13 mm)

Radius - Max:

Shower Ledge Min 2-1/4" (57 mm)

Flat:

Shower Wall Min 2-7/8" (73 mm)

Flat:

#### **Notes**

Install this product according to the installation instructions.

The vertical opening should be a minimum of 73-13/16" (1875 mm) to allow for installation clearance.

