


▲ Designate proper finish suffix

55100-▲
SureDock™ Magnetic
Docking Mount



Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-58600 Rev. B



see what Delta can do™

- PivotPro™ 3-In-1 Combination Shower
- 7-Spray Setting Hand Shower
- Additional Docking Mount for Hand Shower

FEATURES:

- Touch-Clean® Spray Holes
- H₂Okinetic® PowerDrench® Spray
- MagnaTite® Docking
- ProClean™ Spray Setting
- 360-degree pivoting raincan
- Lumicoat® Finish (-PR models only)
- Lumicoat® Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Max flow rate 1.75 gpm at 80 psi, 6.6 L/min @ 550 kPa (58600-▲)
- Max flow rate 2.5 gpm at 80 psi, 9.5 L/min @ 550 kPa (58600-▲25)
- Certified dual check valves for backflow prevention
- Integrated hand shower docks securely into shower head when not in use
- 3-Way diverter allows for single or shared operation of shower head and hand shower
- Hand shower dial changes spray modes including a pause feature - a non-positive shut-off
- 7 Spray settings include: Full body spray, massaging spray, full body with massage spray, shampoo rinsing spray, H₂Okinetic® spray, ProClean™ spray & pause
- 60" -82" (1524mm -2083mm) metal stretchable hose
- Fits standard 1/2"-14 pipe fitting
- Ball connector swivel angle is 24° (12° per side)
- Raincan rotates 20° (10° per side) for adjustable coverage
- Multi-function hand shower and single function raincan
- Lumicoat® is not applied to the shower hose and ball joint
- PivotPro™ Combination increases shower height by up to 5"

WARRANTY

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ♦
- ASME A112.18.3 ♦
- EPA WaterSense® - Applies to 58600-▲

- ♦ Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company