

FREESTANDING TUB DRAIN



Oatey



Freestanding Tub Drain

The Oatey Freestanding Tub Drain works with freestanding island center and offset tubs. When installed at rough-in, it provides simple installation between the P-trap and tub — without needing access from below the floor.

Available in ABS, PVC or cast iron with a plastic or stainless steel flange, this drain is compatible with brass or Schedule 40 tailpieces.

Oatey offers a carefully curated portfolio of thoughtfully designed, exceptionally engineered bath accessories that enhance both the form and function of every bath experience.



Easy, Fast Installation

- Simplifies rough-in installation between P-trap and tub
- Eliminates “stub out” method and the need to access the drain from below the floor



Universal Compatibility

- Universal drain for freestanding/island center and offset tubs
- Compatible with brass or Schedule 40 tailpieces



Compact Size

- Compact size allows the drain to fit inside 8 in., 10 in. and 12 in. joists
- Fits inside 4 in. hole saw opening, making this drain great for remodels



Jobsite Ready

- Pre-installed, tool-free 1/4-turn test plug allows for testing up to 40 ft. of head
- Easy-to-grab protective cap keeps tile from being installed over the open drain and can be easily removed with channel locks



Freestanding Tub Drain Body
& Cherne® Quarter-Turn Test Plug



Protective Cap



Flanged & Threaded
Brass Tailpieces



Slip Joint Nut
& Washer



PVC or ABS Threaded
Tailpiece Adapter



PVC or ABS
Adapter



Lubricant

Each kit includes:

- Freestanding tub drain body
- Protective cap
- 1.5 in. X 2 in. Schedule 40 PVC or ABS adapter
(Adapter not included with cast iron drain body)
- 1.5 in. X 8 in. flanged brass tailpiece
- 1.5 in. X 8 in. threaded brass tailpiece
- Slip joint nut
- Washer
- 1.5 in. Schedule 40 PVC or ABS threaded
tailpiece adapter *(both PVC and ABS adapter
included with cast iron drain body)*
- Quarter-turn test plug
- Cutout template
- Lubricant

PATENT PENDING