

PF Shank King™ Combination Nipples

Application:

- This shank design was developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes, where shank retention can be a problem when using conventional band clamps.

Features:

- PF shank King™ Combination nipples have the same shank pattern as found on the PF style cam and groove fittings sold on page 70.



- recommended for discharge and suction service

Not intended for compressed air

- working pressure is given at 70°F maximum

- The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon™ for recommendations.

NPT Threaded end

Size	Working PSI	Plated Steel		316 Stainless Steel	
		Part #	Price/E	Part #	Price/E
2"	250	ST25PF	\$37.80	RST25PF	\$67.15
3"	125	ST35PF	44.95	RST35PF	168.70
4"	100	ST40PF	64.10	RST40PF	175.00
6"	75	ST60PF	140.00	RST60PF	425.00

Note: Beveled ends for welding are also available. Contact Dixon™ for further information.



G

Tuff-Lite™ King™ Combination Nipples

NPT Threaded end

Size	Polypropylene		Price/E	Opt Qty
	Part #			
½"	PPN44 ¹		\$0.73	50
¾"	PPN66 ¹		0.93	50
1"	PPN88 ¹		1.49	25
1½"	HB150		4.85	25
2"	HB200		5.90	24
3"	HB300		17.10	10
4"	HB400		38.75	---

¹ sold in package quantities only

NPT Threaded end

Size	Nylon		Price/E	Opt Qty
	Part #			
1¼"	THN15		\$6.90	25
1½"	THN20		7.50	25
2"	THN25		11.40	20
3"	THN35		26.00	10



PPN



HB



THN